

# P12000



**PULSTAR MANUFACTURING COMPANY**  
P12000  
Phone: 402-693-2599 Fax: 402-693-2681

The 12,000 Series Pump Hoist consists of a 37 ft. self-supporting mast held by two 4" x 48" double acting cylinders. This design eliminates the need for guy cables. Maximum layback is 11 ft. The basic rig consists of 12,000 lb. capacity (6,000 lb. single line), 155 ft. of 1/2" Dyform 18 HP rotation resistant cable, open swage socket with 7 ton hook, hydraulic outriggers, remote control, and double gear pto with direct mount heavy duty gear pump. Maximum single line speed is 140 fpm. (Shipping weight is 3,150 lbs.)

#### Standard Features:

- Self-contained and sealed oil bath **planetary drive**
- In-line cable weights
- 24 gallon oil capacity
- 2,000 Series Char Lynn hydraulic motors (for added efficiency)
- Outside left oriented control handles (increased cargo bay storage)
- 60" rear outrigger width
- Failsafe hydraulic braking
- Failsafe over-center hydraulic holding valves on all winches
- Extra high grade urethane paint
- **Direct drive tailout winch with Hydraulic disc brake and 125 ft. of 3/8" cable**
- Tower Load Status Gauge
- Mast cylinder holding valves

#### Optional Features:

- Sandreel with or without freefall (automotive clutch disc type)
- Power to the rear
- Hydraulic wire winders
- Heavy duty tailgate
- Heavy duty pipe racks
- Front outrigger
- Hydraulic oil cooler

